




VSSJAFC (CC2F) Detachable Double Flange Loose-Sleeve Force-Transmission Joint

Extended detachable double-flange assembly | Installation adjustment, removal access and axial force transmission



VSSJAFC (CC2F) catalog product



Detachable structural / dimensional drawing

Key Supply & Configuration Data

Product Identity	VSSJAFC (CC2F) detachable double-flange loose-sleeve force-transmission joint
Catalog Size Range	DN65-DN3200
Distinct Structure	Additional detachable right-hand flange/body section; longer assembly than standard VSSJAF (C2F)
Face-to-Face L	400 / 420 / 440 / 600 / 650 / 670 / 700 / 730 / 840 mm by DN group
Adjustment Delta L	40 / 50 / 60 / 80 mm by DN group
Catalog Pressure Groups	0.6 MPa and 1.0 MPa flange-connection dimension groups
Main Materials	Body / follower: QT450-10 or Q235A; gasket: NBR / EPDM / CR; limited short pipe: Q235A
Fasteners	Stud: Q235A / 35#; nut: Q235A / 20# catalog reference
Dimension Standard	Catalog note: dimensions meet GB/T 12465-2007

Stock & Custom Production

- Common sizes and standard configurations are available for fast supply / immediate shipment.
- Custom production can start the same day after drawing and specification confirmation.
- DN, face-to-face length, adjustment, flange drilling, materials, coating and detachable connection details can be made to approved project requirements.



Catalog Main Connection Dimensions

Exact Mingchao CC2F catalog dimensions. This extended detachable series is not interchangeable with the compact C2F table.

DN65-DN700

DN / Dw / L / Delta L / 0.6 MPa / 1.0 MPa

公称通径DN Nominal diameter	管子外径DW External diameter of pipe	外形尺寸		法兰连接尺寸 Flange connection size							
		L	▲L	0.6MPa				1.0MPa			
				D	D ₁	n-Th.	b	D	D ₁	n-Th.	b
65	76	400	40	160	130	4-M12	16	185	145	4-M16	20
80	89			190	150	4-M16	18	200	160	8-M16	22
100	114			210	170		18	220	180		24
125	140			240	200	8-M16	20	250	210		26
150	168			265	225		20	285	240	8-M20	26
200	219			320	280		22	340	295		28
250	273			375	335	12-M16	24	395	350	12-M20	28
300	325	420	50	440	395	12-M20	24	445	400	12-M20	28
350	377			490	445		26	505	460	16-M20	30
400	426			540	495	16-M20	28	565	515	16-M24	32
450	480			595	550		28	615	565	20-M24	32
500	530			645	600	20-M20	30	670	620	20-M24	34
600	630	440	50	755	705	20-M24	30	780	725	20-M27	36
700	720			860	810	24-M24	32	895	840	24-M27	40

DN800-DN3200 - Continued

Same columns | flange dimensions exactly as catalog

800	820	600	60	975	920	24-M27	34	1015	950	24-M30	44
900	920			1075	1020	24-M27	36	1115	1050	28-M30	46
1000	1020	650		1175	1120	28-M27	36	1230	1160	28-M33	50
1200	1220			1405	1340	32-M30	40	1455	1380	32-M36	56
1400	1420	670		1630	1560	36-M33	44	1675	1590	36-M39	62
1600	1620			1830	1760	40-M33	48	1915	1820	40-M45	68
1800	1820	700		2045	1970	44-M36	50	2115	2020	44-M45	70
2000	2020			2265	2180	48-M39	54	2325	2230	48-M45	74
2200	2220	730		2475	2390	52-M39	60	2550	2440	52-M52	80
2400	2420			2685	2600	56-M39	62	2760	2650	56-M52	82
2600	2620	840	80	2905	2810	60-M45	64	2960	2850	60-M52	88
2800	2820			3115	3020	64-M45	68	3180	3070	64-M52	94
3000	3020			3315	3220	68-M45	70	3405	3290	68-M56	100
3200	3220			3525	3430	72-M45	76				

注：本尺寸符合GB/T12465-2007标准

Note: the size meets standard GB/T12465-2007.

I

Construction Materials

Component	Qty	Catalog Material
Valve Body	1	QT450-10 / Q235A
Gasket	1	NBR / EPDM / CR
Follower	1	QT450-10 / Q235A
Limited Short Pipe	1	Q235A
Stud	n	Q235A / 35#
Nut	Sn	Q235A / 20#

Selection Note

Specify VSSJAFc (CC2F) when the detachable extended assembly is required. RFQ: DN/NPS, pipe O.D., pressure group/class, flange standard, L, Delta L, medium, materials/coating, quantity and drawing.

For detailed technical requirements, custom configurations or project questions, please contact us.

www.mingchaoft.com | sales@mingchaoft.com WhatsApp: +86 180 0385 3073